

SAY NO TO FIRE

High tensile strength aids bonding and

Available in widths, inside and outside diameters, and

prevents bird-caging.

The **Grippex Self adhesive PVC electrical insulation tape** and it's high tensile strength give the additional benefit of excellent binding properties.



FIRE

RETARDANT

Glutape India Pvt. Ltd.

www.glutape.com





GRIPPEX FR PVC ELECTRICAL INSULATION TAPE

Manufactured as per IS: 7809 Part 3 / Sec - 1 with the best available FR grade Film & Unique proprietary formulation of rubber based adesive. Grippex carries ISI Mark & is tested / approved by ERDA (Electrical research & development association. Component approval centre telecommunications) it ranks amongst the best with an ever growing market and prestigious customers.

ISO 9001: 2008 ACCREDITED PLANT

Products is manufactured by ISO 9001:2008 accredited plant. Quality policy saying, We, at **Glutape India Pvt Ltd**. will strive to continually improve quality of our products & services to satisfy the need of our customer and will adhere to the work schedule on-time and continually improve the effectiveness of the quality management system.

MULTIPLE USE

Primarily meant for use as insulation tape in electrical wiring, it is also used in jointing kit of telecommunication cable, automotive cable harness & many other industrial like tube./ pipe etc.

SPECIAL FEATURES OF GRIPPEX INSULATION TAPE

- Retardant tape- extinguishes the fire before its is propagated.
- High stability and excellent ageing properties
- Moisture and corrosion resistant
- Resistant to Acid, Alkalis, Oil, Grease & Gasoline
- Non-migratory adhesive Not Transferred from one face to another
- Withstands up to 6500 v AC & provides long lasting insulation thus saving from short circuits
- Indoor & Outdoor applications Weather resistant
- High adhesion strength Specially formulated in house made adhesive does not dry or allow the tape to be loosened
- Made out of soft and stretchable PVC film, ideal to be used on any surface irrespective of shapes
- Soft, Stretchy, easy unwinding, good adhesive to adhere
- Excellent mechanical support at high temp. (Up to 80°C)
- Uniform lead free PVC film thickness tape width & assured length

SPECIFICATION

- THICKNESS
 0.125 + 0.025 mm
- ADHESION TO STEEL
 1.6 N / 10 mm width (min)
- ADHESION TO BACKING
 1.3 N / 10 mm width (min)
- TENSILE STRENGTH
 150 N / 10 mm width per mm thick (min)
- ELECTRIC STRENGTH at RT 40 KV/ mm thickness (min)
- ELECTRIC STRENGTH after humid condition
 35 KV/ mm thickness (min)
- FLAMMABILITY
 Self Extinguishing
- INSULATION RESISTANCE
 1 × 10 Öhms /25 mm width (min)

AS PER IS: 7809 part 3 sec. 1 SPECIFICATION

TERMS & CONDITIONS

Supplied in attractive cartons
Supplied in Standard packing only

Can be supplied as per customized & standard sizes

AVAILABLE COLOUR



Dealer Stamp