

SILFIX PU FOAM INSULATION SEALANT

Simplify your insulation and sealing needs with Silfix® PU Foam - easy to apply and designed to last.

NET QUANTITY:

750 grams + 150 grams = 900 grams

SPECIAL OFFER
EXTRA 150 gms
FREE
750-gms
900 gms



ISO Certified Company

+91 9834161900
+91 8779837559



DESCRIPTION:

Discover Silfix® PU Foam Insulation Sealant, the ultimate solution for sealing, bonding, and soundproofing. Its one-component polyurethane foam provides superior thermal and acoustic insulation, even below -10°C . Eco-friendly and moisture-cured, Silfix® ensures easy application and cost-effective construction. Perfect for a wide range of building needs.

APPLICATIONS:

- Seals and insulates doors, windows, and HVAC systems.
- Ideal for gap filling and electric wiring installations. Effective in construction, roofing, and piping applications.
- Strong adhesion to wood, plywood, concrete, metal, and masonry.
- Suitable for indoor and outdoor repair and sealing tasks.
- Secures roof tiles, wall panels, and other construction materials.

STORAGE AND SHELF LIFE:

- Best used within 18 months from the date of manufacture.
- Store in a dry, cool area, ideally between 5°C and 25°C . Keep the can in an upright position to maintain product integrity.

USER GUIDANCE:

- Use: Shake well, apply on clean, slightly moist surfaces within 5°C to 40°C . Protect nearby areas with tape. Fill gaps to 40% and let expand.
- Safety: Wear gloves and goggles. Use in well-ventilated areas, away from flames. If in contact with skin or eyes, wash and seek medical help if needed.
- After Application: Foam dries in 20 mins, fully cures in 24 hrs. Trim or shape as needed. Don't seal in closed cavities.
- Storage & Cleanup: Keep can cool, below 45°C . Don't puncture or heat the can. Clean uncured foam with soap and water. Keep away from children.



Website



Catalogue

+91 9834161900
+91 8779837559

